

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	sue date: 04/17/2023 Revision date: 04/17/2023 Supersedes: 10/28/2022 Version: 1.1		
SECTION 1: Identification of the	substance/mixture and of the company/undertaking		
.1. Product identifier			
Product form	: Mixture		
Trade name	: BRAKE BEST NON-CHLORINATED BRAKE PARTS CLEANER 14 OZ.		
Product code	: BBC8413		
.2. Relevant identified uses of the s	substance or mixture and uses advised against		
Use of the substance/mixture	: Brake Parts Cleaner		
.3. Details of the supplier of the sat	foty data shoot		
O'Reilly Auto Parts 233 South Patterson Springfield, Missouri 65802 T 417-862-2674			
.4. Emergency telephone number			
Emergency number	: CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)		
ECTION 2: Hazards identificatio	on la		
.1. Classification of the substance			
HS US classification			
Flammable aerosol Category 2 Gases under pressure Compressed gas Acute toxicity (oral) Category 3 Acute toxicity (dermal) Category 3 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Categor Reproductive toxicity Category 2 Specific target organ toxicity (single expos Specific target organ toxicity — Single exp Narcosis	H361 Suspected of damaging fertility or the unborn child ure) Category 1 H370 Causes damage to organs		
Specific target organ toxicity (repeated exp ull text of H- and EUH-statements: see sec	exposure		
.2. Label elements			
HS US labeling			
Hazard pictograms (GHS US)			
Signal word (GHS US)			
Hazard statements (GHS US)	: Danger : H223 - Flammable aerosol		
	 H223 - Flaminable actosol H223 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility or the unborn child H370 - Causes damage to organs H373 - May cause damage to organs through prolonged or repeated exposure 		
Precautionary statements (GHS US)	 P201 - Obtain special instructions P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. N smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use. P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray 		

- P301+P310 If swallowed: Immediately call a poison control center, doctor,physician, P302+P352 If on skin: Wash with plenty of soap and water

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.
P307+P311 - If exposed: Call a poison center/doctor.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment: See section 4.1 on SDS
P322 - Specific treatment (see supplemental first aid instruction on this label)
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance wit
local, regional, national, international regulations.

2.3. Other hazards

Other hazards which do not result in : Contains gas under pressure; may explode if heated. None under normal conditions. classification

Unknown acute toxicity (GHS US) 2.4.

No data available

SECTION 3: Composition/Information on ingredients

3.1. **Substances**

- Not applicable
- 3.2. **Mixtures**

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	30 – 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS-No.) 108-88-3	30 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Methanol	(CAS-No.) 67-56-1	30 – 50	Flam. Liq. 2, H225 STOT SE 1, H370
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 – 10	Press. Gas (Comp.), H280

SECTION 4: First aid measures	
I.1. Description of first aid measures	3
First-aid measures general	 Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Ca a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Immediately call a poison center or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persists. Direc contact with the eyes is likely to be irritating.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately cal poison center or doctor/physician.
.2. Most important symptoms and e	ffects, both acute and delayed
Symptoms/effects	: Irritation of the respiratory tract. If you feel unwell, seek medical advice. Causes damage to organs.
Symptoms/effects after inhalation	: Coughing. Irritation of the respiratory tract. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
Symptoms/effects after eye contact	: May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue Redness of the eye tissue. Causes serious eye irritation.
17/04/2022	ENI (Epoliah US) 2/4

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.
	al attention and special treatment needed
No additional information available	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the su	ubstance or mixture
Fire hazard	: Flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
i.3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol Level 2.
SECTION 6: Accidental release mea	
	quipment and emergency procedures
General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.
5.1.1. For non-emergency personnel	
Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.
.1.2. For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures	: Ventilate area.
.2. Environmental precautions	
	fy authorities if liquid enters sewers or public waters.
.3. Methods and material for containm	ent and cleaning up
For containment	: Dam up the liquid spill. Plug the leak, cut off the supply. Contain released product, collect/pump into suitable containers.
Methods for cleaning up	: Store away from other materials.
.4. Reference to other sections	
See Heading 8. Exposure controls and persona	I protection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breath dust,fumes,gas,mist,vapor spray.
Hygiene measures	: Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Observ normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/av exposure and/or contact. Observe very strict hygiene - avoid contact. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling.
7.2. Conditions for safe storage, includ	ing any incompatibilities
Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
In compatible products	: Strong bases. Strong acids.
Incompatible products Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

EN (English US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 Storage area
 : Store in a well-ventilated place.

 7.3.
 Specific end use(s)

Follow Label Directions.

ollow Laber Directions.		
SECTION 8: Exposure controls/personal	protection	
.1. Control parameters		
BRAKE BEST NON-CHLORINATED BRAKE PARTS CLEANER 14 OZ.		
No additional information available		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	9000 mg/m ³	
ACGIH OEL TWA [ppm]	5000 ppm	
ACGIH OEL STEL	54000	
ACGIH OEL STEL [ppm]	30000 ppm	
USA - OSHA - Occupational Exposure Limits	F	
OSHA PEL (TWA) [1]	9000 mg/m ³	
OSHA PEL (TWA) [2]	5000 ppm	
USA - NIOSH - Occupational Exposure Limits	1	
NIOSH REL (TWA)	9000 mg/m ³	
NIOSH REL TWA [ppm]	5000 ppm	
NIOSH REL (Ceiling)	54000 mg/m ³	
NIOSH REL C [ppm]	30000 ppm	
Acetone (67-64-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	1188 mg/m ³	
ACGIH OEL TWA [ppm]	500 ppm	
ACGIH OEL STEL	1782 mg/m ³	
ACGIH OEL STEL [ppm]	750 ppm	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) [1]	2400 mg/m ³	
OSHA PEL (TWA) [2]	1000 ppm	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA)	590 mg/m ³	
NIOSH REL TWA [ppm]	250 ppm	
Methanol (67-56-1)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	262 mg/m ³	
ACGIH OEL TWA ACGIH OEL TWA [ppm]	200 ppm	
ACGIH OEL STEL	328 mg/m ³	
ACGIH OEL STEL [ppm]	250 ppm	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) [1]	260 mg/m ³	
OSHA PEL (TWA) [2]	200 ppm	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA)	260 mg/m ³	
NIOSH REL TWA [ppm]	200 ppm	
NIOSH REL (Ceiling)	325 mg/m ³	
NIOSH REL C [ppm]	250 ppm	
Toluene (108-88-3)	· · ·	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm	
	_> FL	
.2. Appropriate engineering controls		

8.2. Appropriate engineering controls

Appropriate engineering controls
Environmental exposure controls

: Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Avoid all unnecessary exposure.

Materials for protective clothing:

Excellent resistance:

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and ch	emical properties	
Physical state	: Gas	
Appearance	: Liquid.	
Color	: Colourless to light yellow.	
Odor	: Solvent-like odour. Strong.	
Odor threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Melting point	: < -78.9 °C (Lowest Component-Acetone)	
Freezing point	: No data available	
Boiling point	: 56 °C (Lowest Component-Acetone)	
Flash point	: -18 °C (Lowest Component-Acetone)	
Auto-ignition temperature	: 385 °C (Lowest Component-Acetone)	
Decomposition temperature	: No data available	
Flammability	: No data available	
Vapor pressure	: No data available	
Relative vapor density at 20 °C	: No data available	
Relative density	: 0.82	
Solubility	: Moderately soluble in water.	
Partition coefficient n-octanol/water (Log Pow)	: No data available	
Partition coefficient n-octanol/water (Log Kow)	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: Heating may cause a fire or explosion.	
Oxidizing properties	: No data available	
Explosion limits	: No data available	
9.2. Other information		
VOC content	: 70 %	
Gas group	: Compressed gas	
CECTION 40. Stability and recetivity		

SECTION 10: Stability and reactivity 10.1. Reactivity No additional information available

Chemical stability

10.2.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

0.2. Chemical stability	
lammable aerosol. Contains gas under pre gnition.	ssure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of
0.3. Possibility of hazardous reactio lot established.	ns
0.4. Conditions to avoid	
Direct sunlight. Extremely high or low tempe	ratures. Heat. Sparks. Open flame. Overheating.
0.5. Incompatible materials	
strong acids. Strong bases.	
0.6. Hazardous decomposition prod	licts
oxic fume Carbon monoxide. Carbon dio	
SECTION 11: Toxicological inform	nation
1.1. Information on toxicological effe	
	5010
Acute toxicity (oral)	: Toxic if swallowed.
Acute toxicity (dermal)	: Toxic in contact with skin.
Acute toxicity (inhalation)	: Not classified
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	30000 ppm/4h (Rat; Experimental value)
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	20000 mg/kg body weight
ATE US (gases)	30000 ppmV/4h
ATE US (vapors)	71 mg/l/4h
ATE US (dust, mist)	71 mg/l/4h
Methanol (67-56-1)	
LD50 oral rat	≥ 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 Inhalation - Rat	128.2 mg/l/4h Air
ATE US (dermal) ATE US (vapors)	17100 mg/kg body weight 128.2 mg/l/4h
ATE US (dust, mist)	128.2 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	 > 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value Inhalation (vapours))
ATE US (oral)	5580 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
L	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/effects	: Irritation of the respiratory tract. If you feel unwell, seek medical advice. Causes damage to organs.
Symptoms/effects after inhalation	: Coughing. Irritation of the respiratory tract. Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin.
Symptoms/effects after eye contact	: May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

Toxicity 12.1.

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
LC50 - Fish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)	
Acetone (67-64-1)		
LC50 - Fish [1]	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)	
EC50 - Crustacea [1]	8800 mg/l (48 h; Daphnia pulex)	
LC50 - Fish [2]	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
TLM - Fish [1]	13000 ppm (96 h; Gambusia affinis; Turbulent water)	
TLM - Fish [2]	> 1000 ppm (96 h; Pisces)	
Threshold limit - Other aquatic organisms [1]	3000 mg/l (Plankton)	
Threshold limit - Other aquatic organisms [2]	28 mg/l (Protozoa)	
Threshold limit - Algae [1]	7500 mg/l (Scenedesmus quadricauda; pH = 7)	
Threshold limit - Algae [2]	3400 mg/l (48 h; Chlorella sp.)	
Methanol (67-56-1)		
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi- static system, Fresh water, Experimental value, Locomotor effect)	
Toluene (108-88-3)		
LC50 - Fish [1]	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal)	

12.2. Persistence and degradability

BRAKE BEST NON-CHLORINATED BRAKE PARTS CLEANER 14 OZ.			
Persistence and degradability	Not established.		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
Persistence and degradability	Biodegradability: not applicable. Not established.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
Acetone (67-64-1)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance		
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance		
ThOD	2.2 g O ₂ /g substance		
BOD (% of ThOD)	(20 day(s)) 0.872		
Methanol (67-56-1)			
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water. Not established.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)				
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O ₂ /g substance			
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance			
ThOD	1.5 g O ₂ /g substance			
Toluene (108-88-3)				
Persistence and degradability	Readily biodegradable in water.			
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance			
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance			
ThOD	3.13 g O ₂ /g substance			
12.3. Bioaccumulative potential				
BRAKE BEST NON-CHLORINATED BRAKE PA	ARTS CLEANER 14 OZ.			
Bioaccumulative potential	Not established.			
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4). Not established.			
Acetone (67-64-1)				
BCF - Fish [1]	0.69 (Pisces)			
BCF - Other aquatic organisms [1]	3			
Partition coefficient n-octanol/water (Log Pow)	-0.24 (Test data)			
Bioaccumulative potential	Not bioaccumulative. Not established.			
Methanol (67-56-1)				
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)			
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)			
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.			
Toluene (108-88-3)				
BCF - Fish [1]	90 (3 day(s), Leuciscus idus, Static renewal, Fresh water, Experimental value, Fresh weight)			
Partition coefficient n-octanol/water (Log Pow)	2.73 (Experimental value, 20 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).			
12.4. Mobility in soil				

Carbon Dioxide, Liquefied, Under Pressure (124-38-9) Ecology - soil Not applicable (gas) Acetone (67-64-1) Surface tension 0.0237 N/m (20 °C) Methanol (67-56-1) Surface tension No data available in the literature Organic Carbon Normalized Adsorption -0.89 - -0.21 (log Koc, Calculated value) Coefficient (Log Koc) Ecology - soil Highly mobile in soil. Toluene (108-88-3) Surface tension 27.73 mN/m (25 °C, 0.05 %) Organic Carbon Normalized Adsorption 2.3 (log Koc, Calculated value) Coefficient (Log Koc) Low potential for adsorption in soil. Ecology - soil 12.5. Other adverse effects Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations	3
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

: Avoid release to the environment.

Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT) In accordance with DOT

In accordance with DOT	
US DOT (ground) (DOT)	: UN1950 Aerosols, 2.1
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number	: 126
Other information	: No supplementary information available.
Transport by sea	
UN-No. (IMDG)	: 1950
Class (IMDG)	: 2.1 - Flammable gases
Air transport	
UN-No. (IATA)	: 1950
Proper Shipping Name (IATA)	: Aerosols
Class (IATA)	: 2.1 - Gases : Flammable

SECTION 15: Regulatory information 15.1. US Federal regulation

5.1. US Federal regulations			
BRAKE BEST NON-CHLORINATED BRAKE PARTS CLEANER 14 OZ.			
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard		
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)		
Listed on the United States TSCA (Toxic Substar	nces Control Act) inventory		
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard		
Acetone (67-64-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313			
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard		
Methanol (67-56-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313			
CERCLA RQ	5000 lb		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard		
SARA Section 313 - Emission Reporting	1 %		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

BRAKE BEST NON-CHLORINATED BRAKE PA	ARTS CLEANER 14 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
Listed on the Canadian DSL (Domestic Substances List)			
Acetone (67-64-1)			
Listed on the Canadian DSL (Domestic Substanc	es List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Methanol (67-56-1)			
Listed on the Canadian DSL (Domestic Substanc	es List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

EU-Regulations

Acetone (67-64-1)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methanol (67-56-1)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.2.2. National regulations

Acetone (67-64-1)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on KECL/KECI (Korean Existing Chemicals Inventory)	
Methanol (67-56-1)	

Listed on EPA Hazardous Air Pollutant (HAPS)

15.3. US State regulations

	ILORINATED BRAKE PARTS	ŭ		
•	sition 65 - Carcinogens List	Yes		
U.S California - Propo Toxicity	sition 65 - Developmental	Yes		
U.S California - Propo Toxicity - Female	sition 65 - Reproductive	No		
U.S California - Propo Toxicity - Male	sition 65 - Reproductive	Yes		
State or local regulations		U.S California - Proposition 65		
Carbon Dioxide, Lique	fied, Under Pressure (124-38	-9)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Acetone (67-64-1)				·
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	Yes	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
Toluene (108-88-3)	•	• •		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Carbon Dioxide, Liquefied	, Under Pressure (124-38-9			
State or local regulations				
U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S New York City – Right to Know Hazardous Substances List U.S Pennsylvania - RTK (Right to Know) List Acetone (67-64-1)				
State or local regulations				
U.S California - Proposition 65 U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List				
Methanol (67-56-1)				
State or local regulations				
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S. – New York City – Right to Know Hazardous Substances List				

SECTION 16: Other information

Other information

: NFPA Aerosol Level 3. None.

Full text of H-phrases:

H223	Flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.	
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.	
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.	
Hazard Rating		
Health	: 2 Moderate Hazard - Temporary or minor injury may occur	
Flammability	: 3 Serious Hazard	
Physical	: 1 Slight Hazard	
17/04/2023	EN (English US)	11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protection

: B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.