FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)

FEL-PRO INSTALLATION TIPS

AXLE HOUSING

CLEAN MATING SURFACES of all foreign material including old gaskets, RTV and oil. You may wish to use a degreaser.

TO ASSIST IN ALIGNMENT AND SEALING DURING ASSEMBLY, apply a thin coat of gasket sealer to both sides of gasket(s).

© 2007 Federal-Mogul Corporation Printed in U.S.A.
Form No. I-1352 (Rev. 5/07)