



# COMPLETE™ Full Synthetic Automatic Transmission Fluid

WITH LXE® TECHNOLOGY

LUBEGARD® COMPLETE™ Full Synthetic ATF is a world-class lubricant formulated for outstanding performance and efficiency in meeting or exceeding OEM requirement for reduced viscosity.

Lubegard's unique, proprietary LXE® Technology provides superior wear protection with improved frictional and shear stability (high film strength for the life of the fluid).

This unique technology prevents and eliminates torque converter shudder, improves shift quality and imparts excellent torque carrying capacity for long clutch and component life. LXE® Technology is seal and o-ring friendly, ideal for new, older, and higher-mileage vehicles.

Lubegard® COMPLETE™ Full Synthetic ATF is recommended for all automatic transmissions that require a fully formulated low viscosity ATF with exceptional performance and uncompromising protection. It is engineered to meet or exceed OEM requirements where lower viscosity is required.

## BENEFITS:

- » World class replacement for synthetic low viscosity ATF.
- » Backward compatible to replace DEXRON® fluids in older automatic transmissions that call for DEXRON® as well as Honda applications that call for Z-1® ATF.
- » Formulated with LXE® Technology to meet OEM requirements for shear stability, long term frictional stability, superior shift quality and anti-shudder properties.
- » Seal-friendly LXE® Technology restores seal flexibility and performance to older and high mileage transmissions.
- » Cures sluggish transmission performance on cold mornings.
- » The #1 technology used and endorsed by transmission shops for 30 years now available as a world class service solution for automatic transmissions.

**SEE BACK FOR A COMPLETE LISTING OF COMPATIBLE ATFs**



69005 »



69032 »

## AVAILABILITY:

Stock No.	Unit Size	Case/Qnty
69032	32 oz. (946 mL)	6/c
69005	6 gal. (22.7 L)	n/a
69055	55 gal.	n/a
69275	275 gal. tote	n/a
69330	330 gal. tote	n/a



**TYPICAL PROPERTIES:**

PROPERTY	ASTM TEST METHOD	DATA
Viscosity @ 40° C, cSt	D445	31.00
Viscosity @ 100° C, cSt	D445	6.10
Viscosity Index	D2270	150
Flash Point, COC, °C (°F)	D92	208 (406)
Pour Point, °C (°F)	D97	-48 (-54)
Color	D1500	Red
Gravity, °API	D4052	32.9

**LUBEGARD COMPLETE™ Full Synthetic Transmission Fluid is compatible with the following ATF's:**

**ACURA**

ATF Z-1  
ATF DW-1

**AISIN**

M315  
AW-1  
3309

**AUDI**

Esso LT71141  
G 052 990 A2  
G 052 162 A1, A2  
G 055 025 A2  
G 055 005 A2  
G 055 162 A2  
G 055 540 A2  
G 055 182 A2  
G 060 162 A2

**Allison**

C-3  
C-4  
TES-295  
TES-389

**BMW**

83 22 0 024 359  
83 22 0 026 922  
83 22 0 142 516  
83 22 2 152 426  
83 22 2 163 514  
83 22 0 397 114  
83 22 9 400 272  
83 22 9 400 275  
83 22 0 403 249  
83 22 9 407 765  
83 22 9 407 807  
83 22 9 407 858  
83 22 9 407 859

**CATERPILLAR**

Power Shift TO-2  
Power Shift TO-4

**CHRYSLER**

Mopar ATF+3 (7176)  
Mopar ATF +4 (9602)  
Mopar ATF+5  
Mopar AS68RC  
05127382AA  
Shell 3403  
Shell L12108

**DAEWOO**

LT 711141

**DAIHATSU**

Alumix Multi

**EAGLE**

ATF+3  
ATF+4

**FIAT**

MOPAR AW1

**FORD**

MERCON® SP  
MERCON® LV  
ESR-M2C-163-A2  
FNR5 ATF  
XT-8-QAW  
XT-9-QMM5

**GENERAL MOTORS**

DEXRON, II, II-E, III, III-G,  
III-H  
DEXRON VI  
GM 12378515  
GM 88900925

**HONDA**

Honda Genuine Z-1  
Honda Genuine DW-1

**HYUNDAI**

SP-III ATF  
SP-IV ATF  
NWS 9638  
Apollo ATF Red 1K

**INFINITI**

Matic D  
Matic J  
Matic K  
Matic S

**ISUZU**

Isuzu Besco ATF-II, III  
Isuzu Genuine Fluid

**JAGUAR**

LT 71141  
JLM 20238  
Shell 3403  
Idemitsu K17  
8342

**JEEP**

ATF+3  
ATF+4  
Shell 3403  
JWS 3309

**KIA**

Kia SP-II, III, IV, VI  
Kia Appolo Oil ATF Red-1K

**LAND ROVER**

LT 71141  
Texaco N402  
Shell 1375.4  
AW1

**LEXUS**

Type WS

**MAZDA**

ATF M-3  
ATF M-V  
0000-77-114E-01  
0000-77-122E-01  
0000-77-120E-0

**MERCEDES BENZ**

MB 001 989 21 03-10  
MB 001 989 68 03-10  
MB 236.1  
MB 236.12  
MB 236.14/Shell 2634  
MB 236.2  
MB 236.5  
MB 236.6  
MB 236.7  
MB 236.8  
MB 236.81  
MB 236.9

**MINI**

MC 83 22 0 402 413

**MITSUBISHI**

Diamond SP-II, III  
Dia Queen J2  
Dia Queen J3

**NISSAN**

Nissan Matic-D  
Nissan Matic-J  
Nissan Matic-S  
Nissan-W

**PORSCHE**

000 043 304 00  
Esso LT 71141  
Shell ATF 3403

**SAAB**

93 160 393  
93 165 146  
93 165 147  
Saab Aporoil

**SATURN**

21005966  
22689186

**SCION**

Genuine WS

**SUBARU**

K0140Y0700  
SOA868V9241

**SUZUKI**

Suzuki 3317  
Suzuki 3309  
Suzuki Matic J  
Suzuki Matic S

**TOYOTA**

Toyota Type WS

**VOLKSWAGEN**

G 052 025 A2  
G 052 162 A1  
G 052 162 A2  
G 055 025 A2  
G 052 990 A2

**VOLVO**

1161521  
1161540  
1161641  
97340  
97341  
31 256 774

All trademarks are property of their respective owners.