



PRODUCT BULLETIN

O'REILLY GLOBAL AUTOMATIC TRANSMISSION FLUID

DESCRIPTION:

Global ATF is a premium fluid designed for automatic transmissions of all North American, European, and Asia-Pacific-made vehicles. **Global ATF** provides exceptional oxidation, wear, frictional stability, and anti-shudder properties required in today's high performance transmissions. It also designed to deliver premium performance in older transmissions.

APPLICATIONS:

Global ATF meets or exceeds requirements of Ford's Mercon V and will perform in Mercon SP, Dexron-VI and Toyota WS applications. It is suitable for Chrysler vehicles where ATF+4 and ATF+3 are required and can also be used where fluids meeting Ford ESP-M2C138CJ or Ford M2C166-H specifications are required. **Global ATF** is also recommended for Mercedes transmissions. It exceeds Allison C4 specifications.

Not recommended for use where Ford Type F fluid is required.

Typical Test Data		
Specific Gravity @ 60°F (H ₂ O=1)	0.86-0.88	
Viscosity, @ 100°C cSt	7.6	
Brookfield Viscosity, cP, max	13,000	
Pour Point, °C(F)	<-43(-45)	
Flash Point, °C(F)	350(177)	
Color and Appearance	Red Liquid	
Containers Packaged	O'Reilly Part No.	Mfg. Part No.
Cases-32oz/12pk	GLOBAL	80049
Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.		

O'REILLY GLOBAL AUTOMATIC TRANSMISSION FLUID

Detailed list of recommended specifications is below:

<i>Manufacturer</i>	<i>Specification</i>
Acura	ATF-Z1 (Except in CVTs)
Allison	C-4
Audi	G-055-025-A2
BMW	LA2634,LT71141;TexacoETL-7045-E, ETL-8027B, Shell M1375.4
Chrysler	ATF+4®, ATF+3®, ATF+2®, ATF+®
Ford	MERCON SP®, MERCON LV®, MERCON V®,MERCON®,XT-9QMM5
General Motors	DEXRON VI®, DEXRON III®, 9986195, Type A, Suffix A (TASA)
Honda	ATF-Z1 (except in CVTs)
Hyundai	SP-II, SP-III
Idemitsu	K17
Infinity	Matic-D, Matic-J, Matic-K
Isuzu	Genuine
Jaguar	Shell M1375.4
Kia	All Specifications
Land Rover	Texaco N402, Shell M1375.4
Lexus	Type T, T-III, T-IV
MAN	339F
Mazda	ATF M-V
Mercedes Benz	Sheet 236.x
Mitsubishi	Diamond SP-II, SP-III
Nissan	Matic-D, Matic-J, Matic-K
Saab	Transmax J
Subaru	All specifications
Toyota	Type T, T-III, T-IV
Voith	55.6335.32 (G607)
Volvo	All specifications
Volkswagen	TL052-162, G 052-990, G 052-025-A2, G 052-162-A1
ZF	TE-ML 03D, 04D, 14A, 14B, 16L, 17C
Various(Aisin-Warner Transmissions)	JWS-3309

Additional Technical Support Available @ 866-287-0110