



PRODUCT BULLETIN

MULTI-VISCOSITY AW HYDRAULIC OIL

DESCRIPTION AND APPLICATIONS: **O'REILLY MULTI-VIS AW Hydraulic Oil** is formulated with polymers and premium additives to provide a wider operating temperature range than standard hydraulic oils. It offers high viscosity index, anti-wear, rust, corrosion, and oxidation protection. It is recommended for heavy duty applications, such as excavators, wheel loaders, garbage trucks, snow plows, utility lift trucks and hydraulic cranes.

Typical Test Data		
Viscosity Specifications	32-46-68	
ISO Grade	46	
API Gravity (60°F)	.8740	
Oxidation Life, min. hrs	3000	
Viscosity, cSt @ 40°C	41.4-50.6	
Viscosity Index, Min	125	
Flash Point, °F, Min	395	
Pour Point, °F, Max	-33	
Color	0.5	
Containers Packaged	O'Reilly Part Numbers	Mfg. Part Numbers
Pail-5 gallon	80024	80024
Drum-55 gallon	80043	80043

Product Claims: **O'REILLY MULTI-VIS AW Hydraulic Oil** is recommended for use in hydraulic systems made by major manufacturers, including Eaton Fluid Power, Joy, Jeffrey, Sperry Vickers, Hagglunds-Denison, Cincinnati Machine and others. It meets or exceeds the requirements of:

- * AFNOR E 48-603,
- * Dennison HF-1, HF-2, HF-0
- * Cincinnati Machine P-68, P-69, P-70
- * General Motors LH-04-1; LH-06-1; LH-15-1
- * Racine, variable volume vane pumps
- * Vickers I-286-S, M-2950-S
- * DIN 51524, part 2
- * Jeffrey No. 87
- * Ford M-6C32
- * B.F.Goodrich 0152
- * Lee-Norse, 100-1

Additional Technical Support Available @ 866-287-0110